

UK DECLARATION OF PERFORMANCE

Regulation (EU) 2016/426

No.: 12

- | | | | |
|---|---|---|--|
| 1. Unique identification code of the product-type | Q-Tee II Gas, Q-Tee II C Gas | | |
| 2. Type | Balanced Flue Gas Stoves | | |
| 3. Intended use | Domestic room heater | | |
| 4. NPD Manufacturer | RAIS A/S
Industrivej 20, Vangen
DK-9900 Frederikshavn,
Denmark | Telephone
Telefax
Webmail
Homepage | +45 98 47 90 33
+45 98 47 92 91
kundeservice@rais.dk
www.rais.com |
| 5. Authorised representative | n/a | | |
| 6. System of assessment
AVCP | System 3 | | |
| 7. Notified body | The notified laboratory
Notified Body number : 2575 | INTERTEK Italia S.p.A.
Via Guido Miglioli 2/A
20063 Cernusco sul Naviglio - Milano (MI) Italy | |
- performed the determination of the product type on the basis of type testing under system 3 and issued test report

Report number a. 102929617LHD-001

8. Declared performance Harmonized technical specification: BSEM 613: 2001+A1:2008

Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	Q-Tee II Gas Q-Tee II C Gas
Distance to combustible materials	Rear	50
Minimum distances [mm] <i>For other installation settings see instruction manual</i>	Sides	250
	Front	700
Risk of burning fuel falling out	N/D	
CO-emission of combustion products	31 ppm (G20@20 full All)	
NOx emission	23 ppm (G20@20 full All)	
Surface temperature	Pass	
Electrical safety	Pass	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	291°C (G20@20 full All)	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	8.2 kW (G20@20 full All)	
Room heating output	8.2 kW (G20@20 full All)	
Water heating output	- kW	
Energy efficiency ¹⁾	78.3 % (G20@20 full All)	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date (DMY) 18-11-2022



 Signature