



- A. Open the fuel tank lid
- B. Open a canister of bioethanol. Insert the hose (1) without quick coupling into the canister.
- C. First guide the hose with the quick coupling (2) up to the stove's tank filler and insert it until it clicks and locks into place.
- D. When both hoses are positioned correctly, the plug (3) can then be inserted.
Once the connector is in place, the pump will start filling. Wait until the tank is full.
- E. The fireplace is equipped with a sensor that switches off the pump when the bioethanol reaches a certain level.
This mechanism helps avoid the risk of overfilling the tank.
- F. When the pump has stopped, first remove the plug - then the quick coupling. The quick coupling is released by pressing the button (4).

IMPORTANT: Follow the instructions in the sequence!

PRODUCTINFO:

Litres per minute:	3.1L
Pressure:	5.5 bar
Volt/Amps:	12V
Dimensions:	LxWxH 100x100x190mm
Material:	Primarily made of powder-coated aluminium and PLA plastic.
Finish:	Black
Weight:	1.500gr

BIOETHANOL

For anvendelse og information om bioethanol, besøg venligst: decoflame.dk.
Bemærk venligst, at bioethanol er afgørende for korrekt brug og garantien på dit produkt.

Der tages forbehold for tastefejl, trykfejl og tekniske fejl samt produktions- og produkttolerancer.

Decoflame ApS forbeholder sig retten til at foretage ændringer uden forudgående varsel. Vi henviser til Decoflames Almindelige Salgs- og Leveringsbetingelser.